




## BEARING-MALAYSIA SDN.BHD.



7210 BEP Bearing 2D drawings and 3D CAD models

50 mm x 90 mm x 20 mm SKF 7210 BEP  
Angular contact ball bearing

Bearing No. 7210 BEP

Size	90x50x20 mm
Bore Diameter	90 mm
Outer Diameter	50 mm
Width	20 mm
d	50 mm
D	90 mm
B	20 mm
d <sub>1</sub>	65.75 mm
d <sub>2</sub>	57.68 mm
D <sub>1</sub>	75.15 mm
a	39 mm
r <sub>1,2</sub> - min.	1.1 mm
r <sub>3,4</sub> - min.	0.6 mm
d <sub>a</sub> - min.	57 mm
D <sub>a</sub> - max.	83 mm
D <sub>b</sub> - max.	85.8 mm
r <sub>a</sub> - max.	1 mm
r <sub>b</sub> - max.	0.6 mm
Basic dynamic load rating - C	37.7 kN
Basic static load rating - C <sub>0</sub>	28.5 kN
Fatigue load limit - P <sub>u</sub>	1.2 kN
Reference speed	8500 r/min
Limiting speed	8500 r/min
Calculation factor - k <sub>r</sub>	0.095



## BEARING-MALAYSIA SDN.BHD.

Calculation factor - $k_a$	1.4
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - $Y_0$	0.52
Calculation factor - $Y_1$	0.55
Calculation factor - $Y_2$	0.93
Calculation factor - X	0.35
Calculation factor - $Y_0$	0.26
Calculation factor - $Y_1$	
Calculation factor - $Y_2$	0.57
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.45
EAN	7316576633232
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3   ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	50MM Bore; 90MM



## BEARING-MALAYSIA SDN.BHD.

	Outside Diameter; 20MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3   ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	7210 BEP
Weight / LBS	0.999
Bore	1.969 Inch   50 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Width	0.787 Inch   20 Millimeter
bore diameter:	50 mm
radial static load capacity:	28.5 kN
outside diameter:	90 mm
cage material:	Nylon
overall width:	20 mm
outer ring width:	20 mm
contact angle:	40 °
maximum rpm:	8500 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	37.7 kN



## BEARING-MALAYSIA SDN.BHD.

series:	72
$d_1$	65.75 mm
$d_2$	57.68 mm
$D_1$	75.15 mm
$r_{1,2}$ min.	1.1 mm
$r_{3,4}$ min.	0.6 mm
$d_a$ min.	57 mm
$D_a$ max.	83 mm
$D_b$ max.	85.8 mm
$r_a$ max.	1 mm
$r_b$ max.	0.6 mm
Basic dynamic load rating C	37.7 kN
Basic static load rating $C_0$	28.5 kN
Fatigue load limit $P_u$	1.22 kN
Calculation factor A	0.014
Calculation factor $k_r$	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor $Y_0$	0.26
Calculation factor $Y_2$	0.57
Calculation factor X	0.57
Calculation factor $Y_0$	0.52
Calculation factor $Y_1$	0.55
Calculation factor $Y_2$	0.93
Mass bearing	0.47 kg