



## BEARING-MALAYSIA SDN.BHD.



R16LLB Bearing 2D drawings and 3D CAD models

25,400 mm x 50,800 mm x 12,700 mm NTN  
R16LLB Ball bearing

Bearing No. R16LLB

Size	25.400x50.800x12.700 mm
Bore Diameter	25,400 mm
Outer Diameter	50,800 mm
Width	12,700 mm
d	25,400 mm
D	50,800 mm
B	12,700 mm
C	12,700 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.107
EAN	4547359496215
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Inch



## BEARING-MALAYSIA SDN.BHD.

Long Description	1" Bore; 2" Outside Diameter; 1/2" Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	R16LLB
Weight / LBS	0.236
Outside Diameter	2 Inch   50.8 Millimeter
Bore	1 Inch   25.4 Millimeter
Outer Race Width	0.5 Inch   12.7 Millimeter
bore diameter:	1.0000 in
finish/coating:	Uncoated
outside diameter:	2.0000 in
bearing material:	High Carbon Chrome
overall width:	0.5000 in
cage material:	Steel
bore type:	Round
inner ring width:	0.5000 in
closure type:	Double Sealed
outer ring width:	0.5000 in
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	15000 rpm
snap ring included:	Without Snap Ring
fillet radius:	0.0310 in
internal clearance:	CN
maximum rpm:	16000 RPM



## BEARING-MALAYSIA SDN.BHD.

operating temperature range:	-40 to 250 ° F
standards met:	MIL-G-18709A
dynamic load capacity:	1740 lbf
series:	R
static load capacity:	1170 lbf
manufacturer product page:	<a href="#">Click here</a>
precision rating:	Class 0