



BEARING-MALAYSIA SDN.BHD.

SSR25XW[1,2,3,4,5,6,7,8,9]+
 [96-3000/1]LY[H,P,SP,UP] THK Linear
 Guide Caged Ball Radial SSR Accuracy and
 Preload Selectable

Bearing No.
 SSR25XW[1,2,3,4,5,6,7,8,9]+[96-3000/1]LY[H,
 P,SP,UP]

SSR25XW[1,2,3,4,5,6,7,8,9]+[96-3
 000/1]LY[H,P,SP,UP] Bearing 2D drawings and
 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] W: Standard
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	25
Rail Width W1	23 mm
Mounting Height M	33 mm
Material	Carbon Steel
Rail Length L	96 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	31500
Basic Load Rating Static Rating Co(N)	36400
Allowable Static Moment MA(N m)	258
Allowable Static Moment MB(N m)	158
Allowable Static Moment MC(N m)	330



BEARING-MALAYSIA SDN.BHD.

Block external dimension W	48 mm
Block external dimension L	83 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M6
Mounting Hole Screw Depth	9 mm
Block dimension L1	59.8 mm