



## BEARING-MALAYSIA SDN.BHD.

SHS30V[1,2,3,4,5,6,7,8,9]+[1  
19-3000/1]L[H,P,SP,UP] THK Linear  
Guide Standard Accuracy and Preload Selectable  
SHS Series

Bearing No.  
SHS30V[1,2,3,4,5,6,7,8,9]+[119-3000/1]L[H,P,  
SP,UP]

SHS30V[1,2,3,4,5,6,7,8,9]+[119-30  
00/1]L[H,P,SP,UP] Bearing 2D drawings and 3D  
CAD models

Days to Ship	3 Days
Block Type	[Standard] V: Low Height
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	30
Rail Width W1	28 mm
Mounting Height M	42 mm
Rail Length L	119 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	44800
Basic Load Rating Static Rating Co(N)	66600
Allowable Static Moment MA(N m)	786
Allowable Static Moment MB(N m)	786
Allowable Static Moment MC(N m)	865
Block external dimension	60 mm



## BEARING-MALAYSIA SDN.BHD.

W	
Block external dimension L	106 mm
Mounting hole for blocks	Tapped Holes
Mounting Hole Dimension S(M)	M8
Mounting Hole Screw Depth	8 mm
Block dimension L1	80 mm